




Fully Integrated XXL 60

FDW 8291.1



- Concealed
- Variable fulcrum hinges
- 10 washing programs
- 13 place settings
- Half load option
- Delayed start key
- 2 telescopic racks + cutlery tray
- 3-level upper rack regulation
- Washing temperatures: 38°C ÷ 70°C
- Energy class F (ex A+) - Efficiency class A



Features

The dishwasher has a self-balanced door to maintain the chosen opening position and the 3/1 option (use of detergents with salt and rinse aid). The control panel allows users to select the washing program and warns them when salt and rinse aid are running out. Sound emission of 44 dB (A) re 1 pW and annual electricity consumption of 292 Kwh. The Enersave (ECO) option, combined with the chosen program, reduces energy consumption. Delayed start from 0 to 24 hours. The lower rack holds dishes up to 30 cm in diameter. The safety devices include AcquaStop, level sensors and seals against water leaks.



FULLY INTEGRATED
FDW 8291.1
EAN 8019801021994

DISHWASHING

DISHWASHER



FDW 8291.1	
Type	Variable fulcrum
ENERGY CONSUMPTION	
Efficiency class	F
Washing efficiency class	A
Drying efficiency class	A
Water consumption (litre / cycle)	8.5 L
Estimated annual energy consumption (Kwh)	292
Estimated annual water consumption (litres)	2380 L
Sound level dB (A) re 1pW	44
MAIN FEATURES	
Max place setting no. / IEC	13
Electronic control	•
Delayed start (hours)	0 - 24
Door opening system	Standard
Interior light	-
End-of-cycle detection floor buzzer / infolight	• / •
Multi-tablet arrangement	•
Drying with door auto opening	-
Cold/hot water supply (max 60°C)	• / •
FUNCTIONS AND PERFORMANCE	
Washing temperatures (°C)	38 / 55 / 65 / 70 °C
Washing programs no.	10
Fast cycles / Auto 45 - 65° C	• / •
Half load (for all programs)	Distributed with option
Intensive pan washing (SUPER)	•
Drying system	With residual heat
SAFETY SYSTEM	
Complete water safety	•
No salt indicator	•
No rinse aid indicator	•
Water softener adjustable from 0 to 90 ° dF	•
POWER RATING	
Voltage / Frequency (V - Hz)	220 - 240 / 50
Power cord (m) / Plug	1.4 / •
WEIGHT, DIMENSIONS, INSTALLATION	
Net weight (kg)	42
Height (mm)	818 - 868
Width (mm)	598
Depth (mm)	545
Door regulation	Variable fulcrum height minimum base 10 mm
Built-In Cut Out (W x H x D) mm	600 x 820 x 575
Rear feet front regulation	•