




Fully Integrated 60

FDW 8292.1



- Concealed
- Sliding hinges
- 10 washing programs
- 13 place settings
- Half load option
- Delayed start
- 2 telescopic racks + cutlery tray
- 3-level upper rack regulation
- Washing temperatures: 45 °C ÷ 70 °C
- End-of-cycle door release
- Energy Class E (ex A++) - Efficiency Class A



Features

The dishwasher has a self-balanced door to maintain the chosen opening position and the 3/1 option (use of detergents with salt and rinse aid). The Soft Touch control panel allows users to select the washing program and warns them when salt and rinse aid are running out. Sound emission of 46 dB (A) re 1 pW and annual electricity consumption of 258 Kwh. The Enersave (ECO) option, combined with the chosen program, reduces energy consumption. Delayed start from 0 to 24 hours. The lower rack holds dishes up to 30 cm in diameter. The safety devices include AcquaStop, level sensors and seals against water leaks.



FULLY INTEGRATED
FDW 8292.1
EAN 8019801022007

DISHWASHING

DISHWASHER



FDW 8292.1	
Type	Integrated
ENERGY CONSUMPTION	
Efficiency class	E
Washing efficiency class	A
Drying efficiency class	A
Water consumption (litre / cycle)	12 L
Estimated annual energy consumption (Kwh)	258
Estimated annual water consumption (litres)	3360 L
Sound level dB (A) re 1pW	46
MAIN FEATURES	
Max place setting no. / IEC	13
Electronic control	•
Delayed start (hours)	0 - 24
Door opening system	Standard
Interior light	-
End-of-cycle detection floor buzzer / light	• / -
Multi-tablet arrangement	•
Drying with door auto opening	•
Cold/hot water supply (max 60°C)	• / •
FUNCTIONS AND PERFORMANCE	
Washing temperatures (°C)	45 / 55 / 65 / 70 °C
Washing programs no.	10
Fast cycles	•
Auto 45 - 65°C	•
Half load (for all programs)	Distributed with option
Intensive pan washing (SUPER)	•
Drying system	With residual heat
SAFETY SYSTEM	
AcquaStop	•
No salt indicator	•
No rinse aid indicator	•
Water softener adjustable from 0 to 90 ° dF	•
POWER RATING	
Voltage / Frequency (V - Hz)	220 - 230 / 50
Power cord (m)	1.4
Plug	•
WEIGHT, DIMENSIONS, INSTALLATION	
Net weight (kg)	43
Height (mm)	818 - 868
Width (mm)	598
Depth (mm)	545
Door regulation	Hinges with sliding system
Built-In Cut Out (W x H x D) mm	600 x 820 x 575
Rear feet front regulation	•