




Central Top Hood 52

FPHD 52 TS BK



- Touch controls
- Black Glass Ceramic finish
- Hood with an electric opening/closing device
- Extraction output 700 m³/h
- Extraction power: 5 levels
- Power off timer
- Sound power from 55 to 70 dBA
- Aluminium anti-grease filter
- Filter saturation indicator with oil drip tray
- Non-return valve
- Energy Class A+



Features

Cooktop hood fitted with touch and flap controls and electronic opening/closing system. It can be installed between two induction hobs. This hood ensures high performance even in a small installation area. The anti-grease filters are dishwasher-safe.

Accessories on request:

- HP activated carbon filter - filtering version use

FCHF 45



BLACK GLASS CERAMIC
FPHD 52 TS BK
EAN 8019801022380

EXTRACTION

COOKTOP HOODS



FPHD 52 TS BK	
Type	Cooktop hood
Installation	Cooktop hood
Finish	Black Glass Ceramic
HOOD FEATURES	
Efficiency class	A +
Extraction levels	5
Power off timer	•
Filter saturation indicator with oil-collection tray	•
Aluminium and stainless steel anti-grease filters	•
Minimum air tube \varnothing	\varnothing 150 mm / rect. 220 x 90 (230 x 80)
Airflow non-return valve	•
CONTROLS	
Operating system	Touch control
PERFORMANCE / ELECTRICAL DATA	
Extraction power up to m ³ /h	700 m ³ /h
Sound emissions (dBA)	55 - 70
Estimated annual consumption (kWh)	49
Motor power (W)	168 W
Voltage / Frequency (V - Hz)	220 / 40 - 50 / 60
Power cord (m)	2
Plug (Schuko)	v
ACCESSORIES	
Motor included	•
HP filter for filtering version (on request)	FCHF 45 (X2)
DIMENSIONS	
Width (mm)	520
Height (mm)	140
Depth (mm)	200