




FULGOR
MILANO

PO 9603 G ST X



	97 L
	7.20 MJ/cycle* 2.00 kWh/cycle*
	7.40 MJ/cycle* 2.05 kWh/cycle*

* цикъл · cyklus · portion · zykus · πρόγραμμα · ciclo · tsükkel · ohjelma · ciklus
ciklas · cikls · čiklu · cyclus · cykl · ciclu · program · cykel

65/2014

COD. PROD. FINITO: **FKAFB0050043041**

NUM. ORD.: **XXXXXX**

QTÀ: **1**

DATA INIZIO PROD.: **01/01/2014**

NUM. LINEA: **99**

Product Fiche compliant to commission delegated regulation (EU) No 65/2014

Brand	FULGOR MILANO
Model	PO 9603 G ST X
EEL [%] Energy Efficiency Index - Main cavity ¹⁾	92.3
EEL [%] Energy Efficiency Index - Secondary cavity ¹⁾	
Energy Efficiency Class - Main cavity ²⁾	A
Energy Efficiency Class - Secondary cavity ²⁾	
Energy consumption in conventional mode [kWh/cycle] - Main cavity ³⁾	2.00
Energy consumption in conventional mode [kWh/cycle] - Secondary cavity ³⁾	
Energy consumption in fan-forced mode [kWh/cycle] - Main cavity ³⁾	2.05
Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity ³⁾	
Energy consumption in conventional mode [MJ/cycle] - Main cavity ³⁾	7.20
Energy consumption in conventional mode [MJ/cycle] - Secondary cavity ³⁾	
Energy consumption in fan-forced mode [MJ/cycle] - Main cavity ³⁾	7.40
Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity ³⁾	
Number of cavities	1
Heat source - Main cavity	GAS
Heat Source - Secondary cavity	
Usable volume [l] - Main cavity	
Usable volume [l] - Secondary cavity	97

¹⁾ Energy Efficiency Index calculated according to the volume and energy consumption for each cavity.

²⁾ From A+++ (low consumption) to D (high consumption).

³⁾ Based on the results of standards tests that simulate the thermal properties of food. The consumption will depend on how the appliance is used.

Product Information compliant to commission regulation (EU) No 66/2014

Model identification	Symbol	Value	Unit
PO 9603 G ST X			
FAN FORCED			
Type of oven			
Mass of the appliance	M	51.5	Kg
Number of cavities		1	
Heat source per cavity (electricity or gas)		1	
Volume per cavity - Main cavity	V	97	l
Volume per cavity - Secondary cavity	V		l
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Main cavity	EC _{electric cavity}		kWh/cycle
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity}		kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Main cavity	EC _{electric cavity}		kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Secondary cavity	EC _{electric cavity}		kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity	EC _{gas cavity}	7.20	MJ/cycle kWh/cycle (a)
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}	2.00	MJ/cycle kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity	EC _{gas cavity}	7.40	MJ/cycle kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity	EC _{gas cavity}	2.05	MJ/cycle kWh/cycle
Energy Efficiency Index per cavity - Main cavity	EEL _{cavity}		
Energy Efficiency Index per cavity - Secondary cavity	EEL _{cavity}	92.3	
(a) 1kWh/cycle = 3.6 MJ/cycle			