

SOFIA PROFESSIONAL

INDUCTION FREESTANDING RANGE 36"




CODE ID




FSRC 3605 P MI ED 2F X




 Easy Clean Ceramic Glass

 Booster


 Dual Max

 Pan Detection System

 Residual Heat Sensor

 Soft Closing

 Self Clean Oven


 Multi-Level Cooking

 1 Telescopic Rack

 Cool Touch Door

 Digital Controls

 Meat Probe

 Fast Pre-Heat

PROFESSIONAL COOKER 36"

Professional Digit Control

INDUCTION HOB

5 induction cooking zones
1 Dual Max Power Zone Ø 28 cm
Glass ceramic surface
Pan detection
Booster on all cooking zones
ON / OFF and residual heat indicators (H)
Heating and low temperature functions

OVEN

Electronic multifunction
Digital timer and knobs
Double internal ventilation
Self-cleaning with PYROLYSIS
Door with assisted closing
Interior with black porcelain enamel
1 telescopic rack with total extraction
2 flat metal grids
1 enameled tray with anti-splash
Internal lighting with 3 light points
Internal capacity 161 liters

OPTIONAL ACCESSORIES

INDUKIT 4:
Kit of 4 inductor discs for cooking with
non-specific pans for induction




STAINLESS STEEL
FSRC 3605 P MI ED 2F X



MATTE BLACK STEEL
FSRC 3605 P MI ED 2F MBK

SOFIA

INDUCTION FREESTANDING RANGE



FSRC 3605 P MI ED 2F ...	
Type	Free standing range 36"
Finishing	... X Stainless steel / ... MBK Matte Black
Interiors	Ultra Black Piro
COOKING HOB	
Supply	Induction
Surface	CeraBlack
Pan detector / Safety lock	• / •
Cooling with fans	•
Power Levels	1 - 9
45 ° C melting function	•
Slow cooking at 70 ° C	•
Booster for each zone	•
Residual heat detector H.	•
Error code indicator	•
INDUCTION COOKTOP FEATURES	
Left front power (min - Max) (W)	Ø 230 mm 2300 - 3700 W
Rear left power (min - Max) (W)	Ø 165 mm 1850 - 3000 W
DUAL MAX power (min - Max) (W)	Ø 280 mm 3000 - 5500 W
Central power (min - Max) (W)	Ø 200 mm 1850 - 2600 W
Right front power (min - Max) (W)	Ø 230 mm 2300 - 3700 W
Rear right power (min - Max) (W)	Ø 200 mm 1850 - 3000 W
OVEN	
Type	Electronic multifunction
Double internal ventilation	•
Energy efficiency class	A
Capacity (liters)	161 L
Forced cooling	•
Functions n.	11
PERFORMANCE	
Maximum cooking temperature	290° C
Pyrolysis temperature	460° C
Thermo-ventilated	•
Self-cleaning	•
COMMANDS	
Control system	Digital display with knobs
Automatic shutdown	•
Booster / Meat probe	• / •
SAFETY	
Door lock (during pyrolysis)	•
Cold door / Glass n. / Soft closing	• / 4 / •
ACCESSORIES	
Lighting (Halogen 20 W) n.	3
Flat grids / Telescopic n.	2 / 1
Trays n. / Type	1 / enameled drip pan
POWER RATING	
Max electrical power (W)	3700 W
Voltage / Frequency (V - Hz)	230 - 50
Cord / Plug	• / Schuko
DIMENSIONS	
Width mm	910
Height (min - Max) mm	898 - 947
Depth (mm)	691