




Ceiling-mounted hood 120

FCHD 1200 RC X



- The functions are enabled via remote control
- Stainless steel finish
- Extraction output: 610 m³/h
- 4 suction levels
- Power off timer
- Sound power from 53 to 64 dBA
- LED lighting
- Aluminium anti-grease filters
- Filter saturation indicator
- Non-return valve
- Energy Class B



Features

Ceiling-mounted hood with perimetral extraction (air is extracted along the light panel perimeter). Controls enabled via remote control. Removable light panel for cleaning anti-grease and carbon filters. The anti-grease filters are dishwasher-safe. Also available in white satin-finish glass.

Accessories on request:

- HP activated carbon filter - filtering version use

FCHF 2



STAINLESS STEEL
FCHD 1200 RC X
EAN 8019801023011

EXTRACTION

CEILING-MOUNTED HOODS



FCHD 1200 RC X	
Type	Integrated
Finish	Stainless Steel
Installation	Ceiling-mounted
FEATURES	
Efficiency class	B
Extraction levels	4
Power off timer	•
Anti-grease filter saturation indicator	•
HP filter saturation indicator (filtering)	•
Lighting /	LED / 4 spot
Washable aluminium anti-grease filters	•
Minimum air outlet tube \varnothing	\varnothing 150 mm / rect.
Airflow non-return valve	•
CONTROLS	
Remote control	•
PERFORMANCE / ELECTRICAL DATA	
Extraction power m ³ /h (max)	600
Noise (dBA)	53 - 64
Annual consumption (kWh)	54
Motor power (W)	110
Voltage / Frequency (V - Hz)	230 - 50
Power cord (m) / Plug (Schuko)	2 / •
ACCESSORIES	
Motor included	•
HP filter for filtering version (on request)	FCHF 2
DIMENSIONS	
Space-saving dimensions 200 mm	•
Dim. Product (W x H x D) mm	1200 x 100 - 180 x 650