

Ceiling-mounted hood 90

FCHD 900 RC WH


















- The functions are enabled via remote control
- White Glass finish
- Extraction output: 600 m³/h
- 4 suction levels
- Power off timer
- Sound power from 53 to 64 dBA
- LED lighting
- Aluminium anti-grease filters
- Filter saturation indicator
- Non-return valve
- Energy Class B



Features

Ceiling-mounted hood with perimetral extraction (air is extracted along the light panel perimeter). Controls enabled via remote control. Removable light panel for cleaning anti-grease and carbon filters. The anti-grease filters are dishwasher-safe. Also available in white satin-finish glass.

Accessories on request:

- HP activated carbon filter - filtering version use

FCHF 2



WHITE GLASS FCHD 900 RC WH EAN 8019801023028

fulgor-milano.com **FULGOR** MILANO

CEILING-MOUNTED HOODS



| | FCHD 900 RC WH |
|--|-----------------------|
| Туре | Integrated |
| Finish | White Glass |
| Installation | Ceiling-mounted |
| FEATURES | |
| Efficiency class | В |
| Extraction levels | 4 |
| Power off timer | • |
| Anti-grease filter saturation indicator | • |
| HP filter saturation indicator (filtering) | • |
| Lighting / | LED / 3 spot |
| Washable aluminium anti-grease filters | • |
| Minimum air outlet tube ø ø | Ø 150 mm / rect. |
| Airflow non-return valve | • |
| CONTROLS | |
| Remote control | • |
| PERFORMANCE / ELECTRICAL DATA | |
| Extraction power m³/h (max) | 600 |
| Noise (dBA) | 53 - 64 |
| Annual consumption (kWH) | 54 |
| Motor power (W) | 110 |
| Voltage / Frequency (V - Hz) | 230 - 50 |
| Power cord (m) / Plug (Schuko) | 2/• |
| ACCESSORIES | |
| Motor included | • |
| HP filter for filtering version (on request) | FCHF 2 |
| DIMENSIONS | |
| Space-saving dimensions 200 mm | • |
| Dim. Product (W x H x D) mm | 900 x 100 - 180 x 550 |

fulgor-milano.com FULGOR MILANO