


## ARIA+ induction 60

FHH 600 ID TC BK



- Multifunction Touch Control
- Black Glass Ceramic finish
- 4 cooking zones (2 vertical bridge zones)
- 9 power levels + Booster
- Temp. maintenance function
- Chef function
- Timer
- Power limit (optional)
- Built-In extraction hood
- Extraction booster
- Energy Class A++



## Features


Induction hob with incorporated extraction hood equipped with a patented waterproof motor. One home appliance combining a high-performance hob with an efficient on-surface extraction. The Chef function allows you to differentiate the temperature of the cooking zones. Other functions include: adjustable delayed auto power off, grease filter maintenance warning, a light indicator for the regeneration of activated carbon ceramic filters, and automatic extraction hood power-off when the flap is closed. Moreover, this product comes with the following accessories: an anti-grease filter kit including a surface cleaning scraper. The tube kit and carbon filter kit are available on request:



BLACK GLASS CERAMIC  
FHH 600 ID TC BK  
EAN 8019801032020




DUCT KIT  
FDUCTKIT ARIA +  
EAN 801980103273



CARBON FILTER KIT  
FCHF ARIA+  
EAN 801980103274

# INDUCTION HOBS

GLASS-CERAMIC INDUCTION HOBS



<b>FHH 600 ID TC BK</b>													
Dimension	60												
Technology	Induction B4												
Type of glass	Black Glass Ceramic												
Control type	Touch												
Version	with extraction hood												
Efficiency class	A ++												
<b>INDUCTION HOB TECHNICAL DATA</b>													
Power limiter	•												
Power levels	9 + P												
Booster	5 minutes												
Controls	Multifunction Touch Control												
Power level indication slider	•												
Residual heat indicator for each zone	•												
<b>FUNCTIONS</b>													
	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">"Pause and Resume" function</td> <td style="width: 50%; text-align: right;">Pan detector</td> </tr> <tr> <td>Overheating prot. device</td> <td style="text-align: right;">Tem. lock Controls</td> </tr> <tr> <td>Children lock</td> <td style="text-align: right;">Operation timer</td> </tr> <tr> <td>Melt function (44 °C)</td> <td style="text-align: right;">Aut. fast heating</td> </tr> <tr> <td>Single zone timer</td> <td style="text-align: right;">Chef function</td> </tr> <tr> <td>Buzzer</td> <td style="text-align: right;">Bridge function</td> </tr> </table>	"Pause and Resume" function	Pan detector	Overheating prot. device	Tem. lock Controls	Children lock	Operation timer	Melt function (44 °C)	Aut. fast heating	Single zone timer	Chef function	Buzzer	Bridge function
"Pause and Resume" function	Pan detector												
Overheating prot. device	Tem. lock Controls												
Children lock	Operation timer												
Melt function (44 °C)	Aut. fast heating												
Single zone timer	Chef function												
Buzzer	Bridge function												
<b>4 ZONES</b>													
Zone Dimension	220 X 190 mm												
Bridge function	2 vertical bridge zones												
Max zone power (L9)	2100W												
Booster zone power	3000W												
<b>HOOD TECHNICAL DATA</b>													
Adjustable delayed auto power off	•												
Anti-grease filter maintenance indicator	•												
Ceramic filter regeneration LED indicator	•												
Internal water discharge valve	•												
Dishwasher-safe filter	•												
Regenerable ceramic odour filter removable from the top (optional)	•												
Automatic hood shut-off when the flap is closed	•												
Motor under the glass	•												
Patented waterproof motor	•												
Air exhaust plastic connection	•												
Maximum flow rate (m <sup>3</sup> / h)	700												
Pressure (Pa)	540												
Motor power (W)	220												
Voltage (V)	220 - 240												
Frequency (Hz)	50 - 60												
Sound power max sp. dB(A)	62												
Controls	Multifunction Touch Control												
<b>DIMENSIONS</b>													
Width x Height x Depth (mm)	600 x 249 x 520												
Cutout Width x Depth (mm)	560 x 480												
<b>PERFORMANCE</b>													
Max power absorbed (kW)	7.36												
Voltage (V)	220/240												
Frequency (Hz)	50/60												
<b>INSTRUCTION MANUAL</b>													
Use and installation manual	IT - EN - FR - DE - ES - RU												