




Central Top Hood 51

FPHD 51 TS X



- Touch controls
- Stainless steel finish
- Hood with an electric opening/closing device
- Extraction output 700 m³/h
- Extraction power: 5 levels
- Power off timer
- Sound power from 55 to 70 dBA
- Aluminium anti-grease filter
- Filter saturation indicator with oil-collection tray
- Non-return valve
- Energy Class A+



Features

Cooktop hood fitted with touch and flap controls and electronic opening/closing system. It can be installed between two induction hobs. This hood ensures high performance even in a small installation area. The anti-grease filters are dishwasher-safe.

Accessories on request:

- HP activated carbon filter - filtering version use

FCHF 45



STAINLESS STEEL
FPHD 51 TS X
EAN 8019801022373

EXTRACTION

COOKTOP HOODS



FPHD 51 TS X	
Type	Cooktop hood
Installation	Cooktop hood
Finish	Stainless Steel
HOOD FEATURES	
Efficiency class	A +
Extraction levels	A +
Power off timer	A +
Filter saturation indicator with oil-collection tray	•
Aluminium and stainless steel anti-grease filters	•
Minimum air tube \varnothing	\varnothing 150 mm / rect. 220 x 90 (230 x 80)
Airflow non-return valve	•
CONTROLS	
Operating system	Touch control
PERFORMANCE / ELECTRICAL DATA	
Extraction power up to m ³ /h	700 m ³ /h
Sound emissions (dBA)	55 - 70
Estimated annual consumption (kWh)	49
Motor power (W)	168 W
Voltage / Frequency (V - Hz)	220 / 40 - 50 / 60
Power cord (m)	2
Plug (Schuko)	•
ACCESSORIES	
Motor included	•
HP filter for filtering version (on request)	FCHF 45 (X2)
DIMENSIONS	
Width (mm)	510
Height (mm)	140
Depth (mm)	200