

## Wall-mounted hood 90

FTHD 900 TC X


















- Stainless steel finish
- Extraction output: 730 m³/h
- 4 suction levels
- Power off timer
- Sound power from 47 to 72 dBA
- LED bar lighting
- Baffle anti-grease filters
- Filter saturation indicator
- Non-return valve
- Energy Class A



## **Features**

The T-shaped wall-mounted hood's top can be used as a support base for kitchen utensils. It features high-efficiency baffle anti-grease filters. The LED bar ensures optimal illumination of the hob and can be used as a courtesy light. The anti-grease filters are dishwasher-safe. Also available with a black or white glass front panel.

Accessories on request:

- HP activated carbon filter - filtering version use

FCHF 49



STAINLESS STEEL FTHD 900 TC X EAN 8019801023059

fulgor-milano.com **FULGOR** MILANO

## WALL-MOUNTED HOODS



|  | FTHD 900 TC X              |
|--|----------------------------|
| Tuna   | Visible                    |
| Type   |                            |
| Finish                                       | Stainless Steel            |
| Installation                                 | Wall-mounted               |
| FEATURES                                     |                            |
| Efficiency class                             | A                          |
| Extraction levels                            | 4                          |
| Auto power off                               | • 10 minutes               |
| Anti-grease filter saturation indicator      | •                          |
| HP filter saturation indicator (filtering)   | •                          |
| Lighting                                     | LED bar                    |
| Type of anti-grease filters                  | PRO stainless steel baffle |
| Dishwasher-safe anti-grease filters          | •                          |
| Minimum air outlet tube ø ø                  | Ø 150 mm / rect.           |
| Airflow non-return valve                     | •                          |
| CONTROLS                                     |                            |
| Operating system                             | Touch control              |
| Remote control                               | •                          |
| PERFORMANCE / ELECTRICAL DATA                |                            |
| Extraction power m³/h (max)                  | 730                        |
| Noise (dBA)                                  | 47 - 72                    |
| Annual consumption (kWH)                     | 49                         |
| Motor power (W)                              | 275                        |
| Voltage / Frequency (V - Hz)                 | 230 - 50                   |
| Power cord (m)                               | 2                          |
| Plug (Schuko)                                | •                          |
| ACCESSORIES                                  |                            |
| Motor included                               | •                          |
| HP filter for filtering version (on request) | FCHF 49 (X2)               |
| DIMENSIONS                                   |                            |
| Width (mm)                                   | 900                        |
| Height (mm)                                  | 605 - 1030                 |
| Depth (mm)                                   | 505                        |
| ,  |                            |

fulgor-milano.com FULGOR MILANO