**CLUSTER OVENS** 



## ATMOS Cluster Steam Oven 60

FCLSO 6023 TEM BK




















- Deep Black finish
- Classic Pizza mode + AirFry (oven-frying) function)
- Meat probe
- TFT touch control display
- 1500 ml water tank
- 11 classic cooking functions
- 6 steam cooking functions
- 7 special cooking functions
- 100% steam in 5 minutes
- Soft Closing
- Energy Class A++



## **Features**

ATMOS, FULGOR MILANO's steam oven has 24 cooking functions, ideal for complex and easy preparations. Premium household appliance with an automatic control panel opening system to help you fill the water tank without opening the oven. Numerous recipes are available, even for prolonged cooking (up to 3 hours of continuous steam). Water level sensor and reset notice. Cavity and circuit cleaning and descaling functions.

This product comes with the following accessories: fully removable telescopic rails, a Meat Probe, a stainless steel steam kit (perforated tray and surface with support), an AirFry tray, an enamelled tray, and a flat grill rack.



DEEP BLACK GLASS FCLSO 6023 TEM BK EAN 8019801031993

fulgor-milano.com **FULGOR** MILANO



Type Combined Steam  Dimension 60  Structure - Finish Deep Black  Temperature regulation Electronic  FATURES  Efficiency class A++  Capacity (litres) 65  Forced cooling • •  Meat probe • •  Sizes Timer 12 / 24 - Temperature "C / "F - Weight Kg / lib  Cooking functions Classic 11 Steam 6 Special 7  Max cooking temperature C / "F - Weight Kg / lib  Cooking functions Classic 11 Steam 6 Special 7  Max cooking temperature 250 °C  Grill power (W) 1200 + 1000  Steam cooking autonomy > 3 hours  Water tank capacity 1.5 ! (Topping up without door opening)  Dashboard opening - touch control  FUNCTIONS  Classic Pizza function at 250 °C  Steam cooking from 30 ° to 100 °C  Pre-loaded and editable rec Puff function Low-temperature coo Sous vide Defrost function with st Leavening function Frast recipe selection Leavening function • Steam Cooking function Sous vide Sous		FCLSO 6023 TEM BK				
Dimension   60	Type					
Structure - Finish   Deep Black   Electronic						
Electronic   Ele						
EFATURES   Capacity (litres)   65		·				
Efficiency class		LIGULUTIIG				
Capacity (litres)			^			
Forced cooling						
Mast probe						
Sizes   Timer 12 / 24 - Temperature "C / "F - Weight Kg / lb						
Cooking functions						
Max cooking temperature Gnill power (W) Steam cooking autonomy Water tank capacity Jashboard opening - touch control FUNCTIONS  Classic Pizza function at 250 °C Steam cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Sous vide Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Sous vide Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Sous vide Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Sous vide Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Sous vide Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Defrost function with the cooking from 30 ° to 100°C Pre-loaded and editable rec Low-temperature or Defrost function with the cooking from the cooking fro						
Grill power (W)  Steam cooking autonomy  Water tank capacity  Dashboard opening - touch control  FUNCTIONS  Classic Pizza function at 250 °C  Steam cooking from 30 ° to 100°C  Pre-loaded and editable rec  Puff function  Sous vide  Defrost function with st  Leavening function  CONTROL PANEL  Display   Control type  Fast recipe selection  Languages  FEATURES  Demo Mode  Steam cleaning function  Beep volume setting  Display brightness setting  Descaling function  Descaling function  Descaling function  Descaling function  Event logs (for assista of Cool touch - no. of glass panes  Closure  AOCESSORIES  Side rack levels  Rectangular halogen light (20 W)  Fully removable telescopic ralls  Capacity from the function of the functio		Olassic 11			Opeciai /	
Steam cooking autonomy   S a hours	- :					
Dashboard opening - touch control FUNCTIONS						
Dashboard opening - touch control FUNCTIONS  Classic Pizza function at 250 °C Steam cooking from 30 ° to 100 °C Per-loaded and editable rec Low-temperature coc Sous vide Defrost function with st Leavening function Leavening function Leavening function Leavening function Leavening function TFT 3.5"   MODULAR - Electronic (double full touch keypad) Fast recipe selection Languages FEATURES  Demo Mode Steam cleaning function Beep volume setting Circuit cleaning function Display brightness setting Descaling function Descaling						
Classic Pizza function at 250 °C Steam cooking from 30 °t to 100°C Pre-loaded and editable rec Puff function Low-temperature coo Sous vide Leavening function Leavening function Regeneration (18 CONTROL PANEL Display   Control type Fast recipe selection Languages FFATURES  Demo Mode Steam cleaning function Sealing function Sealing function Languages FFATURES  Demo Mode Steam cleaning function Sealing function Descaling function Sealing function Sealing function Descaling function Sealing function Descaling function Sealing function Descaling function Sealing function Sealing function Descaling function Sealing function Descaling func		1.5 T (Topping up without door opening)				
Classic Pizza function at 250 °C   AirFry (oven-from 1900		•				
Steam cooking from 30 ° to 100°C	FONCTIONS	Classic Direction at 050 °C		AirEnv (avan finina)		
Puff function   Low-temperature code				7 . 7 . 07		
Sous vide		Puff function Sous vide		<u>'</u>		
Leavening function  CONTROL PANEL  Display   Control type Fast recipe selection Languages FEATURES  Demo Mode Demo Mode Desplay brightness setting Descaling function  Col touch - no. of glass panes Closure ACCESSORIES Side rack levels Rectangular halogen light (20 W) Fully removable telescopic rails S. Steel Gastronorm tray Gastronorm tray Flar tracks Frameled tray & 1 Flar tracks DIMENSIONS Product (W x H x D) mm Built-In Cut Out (W x H x D) mm Built-In Cut Out (W x H x D) mm Bussel Frances Bussel Frances Bussel Frances Bussel Frances						
CONTROL PANEL Display   Control type						
Display   Control type	CONTROL DANIEL	Leaverning function			negerieration (160 C)	
Fast recipe selection		TET 2 5"	MODIII AB. Electr	rania (daubla full ta	wich kaynad)	
Languages		TFT 3.5"   MODULAR - Electronic (double full fouch keypad)				
Demo Mode   Steam cleaning function   Beep volume setting   Circuit cleaning function   Display brightness setting   Sabbath in Descaling function   Descaling function   Event logs (for assistation of the property of the				15		
Demo Mode   Steam cleaning function				10		
Beep volume setting Display brightness setting Descaling function Descaling function Descaling function Descaling function Descaling function Descaling function  Event logs (for assistation of touch - no. of glass panes) Colosure ACCESSORIES Side rack levels Side rack levels Side rack levels Fectangular halogen light (20 W) Fully removable telescopic rails S. Steel Gastronorm perforated tray Gastronorm tray 1 Tray support frame 1 Enamelled trays Enamelled tray AirFry 1 Flat racks DIMENSIONS Product (W x H x D) mm S94 x 596 x 560 Built-In Cut Out (W x H x D) mm ELECTRICAL FEATURES Max electrical power Voltage / Frequency (V - Hz) Sababath m Soft closed Scheduler assistation Scheduler assistation Sevent logs (for assistation Sevent logs (for assistation Sababath m Soft closed S	TEATORES	Demo Mode			Steam cleaning function	
Display brightness setting					<del>_</del>	
Descaling function         Event logs (for assistate)           OVEN DOOR           Cool touch - no. of glass panes         3           Closure         soft closed           ACCESSORIES         Side rack levels           Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS         1           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         1           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		Display brightness setting		Sabbath mode		
OVEN DOOR           Cool touch - no. of glass panes         3           Closure         soft closed           ACCESSORIES         Side rack levels           Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS         1           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz				Event logs (for assistance)		
Cool touch - no. of glass panes         3           Closure         soft closed           ACCESSORIES           Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	OVEN DOOR					
Closure         soft closed           ACCESSORIES           Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS         1           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		3				
Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz						
Side rack levels         5 (removable side racks)           Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	ACCESSORIES					
Rectangular halogen light (20 W)         2           Fully removable telescopic rails         1 pair           S. Steel Gastronorm perforated tray         1           Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		5 (removable side racks)				
Fully removable telescopic rails       1 pair         S. Steel Gastronorm perforated tray       1         Gastronorm tray       1         Tray support frame       1         Enamelled trays       1         Enamelled tray AirFry       1         Flat racks       1         DIMENSIONS       1         Product (W x H x D) mm       594 x 596 x 560         Built-In Cut Out (W x H x D) mm       560 x 595 x 560         ELECTRICAL FEATURES       3.50 kW         Voltage / Frequency (V - Hz)       220 - 240 V; 50 Hz	Rectangular halogen light (20 W)					
S. Steel Gastronorm perforated tray       1         Gastronorm tray       1         Tray support frame       1         Enamelled trays       1         Enamelled tray AirFry       1         Flat racks       1         DIMENSIONS         Product (W x H x D) mm       594 x 596 x 560         Built-In Cut Out (W x H x D) mm       560 x 595 x 560         ELECTRICAL FEATURES         Max electrical power       3.50 kW         Voltage / Frequency (V - Hz)       220 - 240 V; 50 Hz						
Gastronorm tray         1           Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz						
Tray support frame         1           Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		1				
Enamelled trays         1           Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	· · · · · · · · · · · · · · · · · · ·	1				
Enamelled tray AirFry         1           Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		1				
Flat racks         1           DIMENSIONS           Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	-	1				
Product (W x H x D) mm         594 x 596 x 560           Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz		1				
Built-In Cut Out (W x H x D) mm         560 x 595 x 560           ELECTRICAL FEATURES         3.50 kW           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	DIMENSIONS					
ELECTRICAL FEATURES           Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	Product (W x H x D) mm		594 x 5	96 x 560		
Max electrical power         3.50 kW           Voltage / Frequency (V - Hz)         220 - 240 V; 50 Hz	Built-In Cut Out (W x H x D) mm		560 x 5	95 x 560		
Voltage / Frequency (V - Hz) 220 - 240 V; 50 Hz	ELECTRICAL FEATURES					
	Max electrical power		3.5	0 kW		
Power cord •	Voltage / Frequency (V - Hz)		220 - 24	0 V; 50 Hz		
	Power cord			•		
Plug Schuko	Plug	Schuko				

fulgor-milano.com FULGOR MILANO