

Enova 90 Induction Hob

FEHK 3605 ID IX


















- Stainless Finish
- Metal Control Knobs with Stainless Finish
- Glass Ceramic Surface
- 5 Cooking Zones (2 vertical bridge zones)
- Pan Detection Sensor
- 9 Power Levels
- BOOST Rapid Preheating
- Child Safety lock
- Keep Warm Function



Features

The Enova cooktop is the perfect blend of cutting-edge technology and sophisticated design. Crafted from solid 15 mm satin-finished aluminum, it stands out for its elegant recessed knobs. Powered by innovative Quantum induction technology, it guarantees high performance, reduced energy consumption, and fast, precise cooking. The cooktop features five cooking zones, each controlled via dedicated knobs, including a high-power 28 cm zone and two zones with a bridge system ideal for larger cookware. Each zone offers adjustable power levels from 1 to 9, along with dedicated functions such as Keep Warm, Rapid Heat, and BOOST. Thanks to its refined design and advanced professional functions, the Enova cooktop is the ideal choice for those seeking an appliance that combines aesthetics and performance.



STAINLESS FINISH FEHK 3605 ID IX EAN 8019801035397

fulgor-milano.com **FULGOR** MILANO

GLASS CERAMIC INDUCTION HOBS



		FEHK 30	605 ID IX		
Type		90 Induction Hob			
Finish		Stainless			
Surface		Glass Ceramic			
INDUCTION PERFORMANCE					
Induction features		Pan Detection System	Child Lock		
		Cooling System	Cooking Level Indicator		
Knobs for power adjustment		•			
Power levels		1-9			
Digital display indicating power level		•			
Melting function at 45°C		•			
Keep warm function at 70°C		•			
Simmering function at 95°C		•			
Booster / Rapid boil function for each zone		•			
Rapid heating		•			
Bridge function		•			
Rear Right		•			
COOKING ZONE FEATURES		Dimensions	Pov	wer	
5 Cooking Zones (2 Bridge Zones)					
1 Front Left	Octa Induction	220 x 180 mm	Level 9 - 2100W	Booster - 3700W	
2 Rear Left	Octa Induction	220 x 180 mm	Level 9 - 2100W	Booster - 3700W	
3 Central Dual Circuit	Round Induction	Ø 280 mm	Level 9 - 2600W	Booster - 5500W	
4 Front Right	Octa Induction	220 x 180 mm	Level 9 - 2100W	Booster - 3700W	
5 Posteriore Destro	Octa Induction	220 x 180 mm	Level 9 - 2100W	Booster - 3700W	
DIMENSIONS					
Width		913 mm			
Height (Without power cable)		66 mm			
Depth		530 mm			
Cut-out Width		840 mm			
Cut-out Depth		500 mm			
ELECTRICAL SPECIFICATIONS					
Maximum Electrical Power (W)		11040W			
Conduit					

fulgor-milano.com FULGOR MILANO